



# SPECIFICATION

## TIKKA T3 BATTUE



TIKKA T3 BATTUE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3 cartridges. Single-column 4-5-shot magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The walnut STOCK is oilfinished as standard and has a buttplate system where the length of pull is adjustable by means of spacers. Matte-lacquered stocks are also available. Straight stock features ambidextrous palm swell.

Special OPEN SIGHTS designed for snaphooting have adjustable rear sight (elevation). Rear sight leaf, bead and rear sight rib are also provided with illuminated dots. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The short, free-floating BARREL is cold hammer-forged.

### TECHNICAL DATA

|                   |                |   |                           |                    |                      |
|-------------------|----------------|---|---------------------------|--------------------|----------------------|
| <b>Action</b>     | <b>caliber</b> | <b>rate of twist</b>                    | <b>Overall length</b>     |                    |                      |
|                   | 308 Win        | 11"                                     | T3                        | 1020 mm (40 3/16") |                      |
|                   | 338 Federal    | 10"                                     | <b>Barrel length</b>      |                    |                      |
|                   | 7x64           | 10"                                     | T3                        | 510 mm (20")       |                      |
|                   | 30-06 Sprg     | 11"                                     | <b>Weight</b>             |                    |                      |
|                   | <b>T3</b>      | 8x57IS                                  | 9.5"                      | T3                 | 3.1 kg (6 13/16 lbs) |
|                   | 9.3x62         | 14"                                     | <b>Cartridge capacity</b> |                    |                      |
| 300 Win Mag       | 11"            | T3 all calibers 4 rounds (1 in chamber, |                           |                    |                      |
| 300 Win Short Mag | 11"            | 3 in clip magazine)                     |                           |                    |                      |