



# SPECIFICATION

## TIKKA T3 BATTUE LITE



TIKKA T3 BATTUE LITE based on a two locking lug T3 action. Bolt features springloaded plunger ejector and it can be easily stripped down for maintenance. Bolt is made of stainless steel.

The single-column detachable clip MAGAZINE holds 3 cartridges. Single-column 4-5-shot magazine is available as accessory (not in Short Mag calibers).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). Safety is two stage type and locks the trigger and the bolt handle when engaged. All models are available with a single-set trigger as option.

The STOCK is made of glass-fiber reinforced copolymer polypropylene and has a buttplate system where the length of pull is adjustable by means of spacers. Straight stock features ambidextrous palm swell.

Special OPEN SIGHTS designed for snaphooting have adjustable rear sight (elevation). Rear sight leaf, bead and rear sight rib are also provided with illuminated dots. Integral rails for the scope mounts are on the top of the receiver. Receiver is also tapped to receive standard (Weaver) scope mount bases.

The short, free-floating BARREL is cold hammer-forged.

### TECHNICAL DATA

Action	caliber	rate of twist	Overall length	
T3	308 Win	11"	T3	1020 mm (40 3/16")
	338 Federal	10"	Barrel length	
	7x64	10"	T3	510 mm (20")
	30-06 Sprg	11"	Weight	
	8x57IS	9.5"	T3	2.8 kg (6 3/16 lbs)
	9.3x62	14"	Cartridge capacity	
	300 Win Mag	11"	T3 all calibers 4 rounds (1 in chamber, 3 in clip magazine)	
300 Win Short Mag	11"			