



TECHNICAL SPECIFICATION TIKKA T3 HUNTER FLUTED BARREL

| | | |
|---|--|----------------------------|
| WEAPON | TIKKA T3 | |
| MODEL | HUNTER FLUTED BARREL | |
| MANUFACTURER | SAKO Ltd., FINLAND | |
| AVAILABLE ACTION SIZES | Right hand / STD Left Hand / Available | |
| OPERATION | Tikka T3 manually operated bolt action | |
| BOLT | 2 locking lugs, plunger ejection | |
| CALIBER / RATE OF TWIST / MAGAZINE CAPACITY | 204 Ruger / 12" / (4 in magazine, 1 in chamber) 222 Rem / 14" / (4 in magazine, 1 in chamber) 223 Rem / 8, 12" / (4 in magazine, 1 in chamber) 22-250 Rem / 14" / (3 in magazine, 1 in chamber) 243 Win / 10" / (3 in magazine, 1 in chamber) 260 Rem / 8" / (3 in magazine, 1 in chamber) 7mm-08 Rem / 9.5" / (3 in magazine, 1 in chamber) 308 Win / 11" / (3 in magazine, 1 in chamber) 25-06 Rem / 10" / (3 in magazine, 1 in chamber) 6.5x55 SE / 8" / (3 in magazine, 1 in chamber) 270 Win / 10" / (3 in magazine, 1 in chamber) 7x64 / 10" / (3 in magazine, 1 in chamber) 30-06 Sprg / 11" / (3 in magazine, 1 in chamber) 7mm Rem Mag / 9.5" / (3 in magazine, 1 in chamber) 300 Win Mag / 11" / (3 in magazine, 1 in chamber) 270 Win Short Mag / 10" / (3 in magazine, 1 in chamber) 300 Win Short Mag / 11" / (3 in magazine, 1 in chamber) | |
| OVERALL WEIGHT w/o ACCESSORIES | T3 / 3.1 kg (6 13/16 lbs) | T3 Mag / 3.2 kg (7 lbs) |
| OVERALL LENGTH | T3 / 1080 mm (42 1/2") | T3 Mag / 1130 mm (44 1/2") |
| BARREL LENGTH | T3 / 570 mm (22 7/16") | T3 Mag / 620 mm (24 3/8") |
| LENGTH OF PULL | Minimum 335mm (13.2") adjustable with spacers | |
| BARREL | Fluted light hunting contour barrel (cold hammer forged) | |
| MAGAZINE | Detachable single row synthetic magazine (T3 short magazine) | |
| SIGHTS | No open sights | |
| OPTICAL SIGHT ATTACHMENT | 17mm dovetail rail | |
| METAL PARTS SURFACE FINISHING | Blued metal parts | |
| STOCK | Matte oiled walnut stock | |
| TRIGGER MECHANISM | Single stage trigger, adjustable pull 1 to 2kg (2 to 4 lbs) (Optional set trigger) | |
| SAFETY | Two stage safety | |
| ACCESSORIES | Manual | |

